

# User Reference Guide


Instant
Issuance System with
Embossing Module



### **Contents**


The CE875 Instant Issuance System	. 3
The Printer with Optional Multi-Hopper	. 4
oad Cards in a Single-Hopper Printer	. 5
Jse the Exception Slot	. 6
oad Cards in a Multi-Hopper Printer	. 7
Jse the Multi-Hopper Exception Slide	. 9
Replace the Color Ink Ribbon1	LO
Replace the Cleaning Sleeve1	<b>L2</b>
Replace the Retransfer Film1	L4
Replace the Indent Ribbon1	16
Replace the Topping Foil1	18
Empty the Embosser Reject Tray2	20
Clear a K1 Horizontal Transport Card Jam2	21
Clear a K2 Vertical Transport Card Jam2	23
Clear a Flipper Card Jam2	24
Clear an Embosser Card Jam2	25
Repair a Broken Ink Ribbon2	26
Repair Broken Retransfer Film2	27
Repair a Broken Indent Ribbon2	28
Repair Broken Topping Foil2	29
Check the Power Connections3	30
Check the Data Connections3	31
Common Printer LCD Messages3	32
Common Embosser LCD Messages3	33
Common Print Quality Concerns3	34
Cleaning Schedule3	35
Jse the Isopropanol Cleaning Card3	36
Jse the Adhesive Cleaning Card3	39
Clean the Printhead4	13
Clean the Printhead Cam Rollers4	17
Notes	19

### The CE875 Instant Issuance System




- A Printer Input Hopper
- B Embosser Output Hopper
- C Front Panel
- D Embosser Supplies Access Door
- E Embosser Lock
- F Printer Lock
- G Printer Access Door
- H User Reference Guide Slot
- I Topping Foil Cartridge
- J Embosser Reject Tray
- K Indent Cartridge

- L Manual Advance Knob (K2)
- M Rear Access Door Release (K3)
- N Vertical Transport Area
- O Retransfer Film Cartridge Release Button
- P Retransfer Cartridge (C2)
- Q Ink Ribbon Cartridge Release Button
- R Ink Ribbon Cartridge (C1)
- S Cleaning Spindle Handle (C3)
- T Manual Advance Knob (K1)



### The Printer with Optional Multi-Hopper



A = Output Hopper

B = Hopper Lock Bars

C = Input Hoppers 1–6

D = Multi-Hopper Lock

E = Lock Bar Release Button (B1)

F = Cartridge Release Buttons


G = Exception Slide

H = Card Weight

I = Cartridge Door

J = Cartridge Door Release Button

# Load Cards in a Single-Hopper Printer



# **Use the Exception Slot**




### Load Cards in a Multi-Hopper Printer

- a
- 1. Unlock the multi-hopper lock.
- 2. Slide the lock bar release button (B1) to the left.
- 3. Rotate a lock bar to the left.









User Reference Guide

#### **Load Cards in a Multi-Hopper Printer**

b

- 4. Press the cartridge release button at the top of the cartridge and open the cartridge door.
- 5. Lift the card weight to the top of the cartridge and pull it forward until it locks in position.
- 6. Load the cards into the cartridge.



Close the cartridge door to release the card weight so that it rests on top of the cards.

Card Weight

d

Repeat for each input hopper cartridge.

Return all locks to the locked position when finished.

### Use the Multi-Hopper Exception Slide

a


Pull out the multi-hopper exception slide and insert the card.



b


Push in the exception slide.

# Replace the Color Ink Ribbon




### Replace the Color Ink Ribbon (cont.)


d



e




t



g

Replace the ink ribbon cartridge in the printer.


# Replace the Cleaning Sleeve



### Replace the Cleaning Sleeve (cont.)




# Replace the Retransfer Film




### Replace the Retransfer Film (cont.)


d



e



f



g


Replace the retransfer film cartridge in the printer.

# Replace the Indent Ribbon






b




C



### Replace the Indent Ribbon (cont.)






e



# Replace the Topping Foil


a





### Replace the Topping Foil (cont.)





d



# **Empty the Embosser Reject Tray**



# Clear a K1 Horizontal Transport Card Jam Single-Hopper System

Unlock the printer and open the printer access door.
Remove the retransfer film cartridge.



Turn the K1 manual advance knob counterclockwise to move the jammed card into the output hopper.

Remove the card through the output hopper.




Replace the retransfer film cartridge and close and lock the printer.

#### Clear a K1 Horizontal Transport Card Jam (cont.)

#### **Multi-Hopper System**

a

- 1. Unlock the printer and open the printer access door.
- 2. Remove the ink ribbon and retransfer film cartridges.
- 3. Locate the card in the printer. Turn the K1 manual advance knob if necessary to access the card.
- 4. Remove the card from the printer.



b

Replace the cartridges and close and lock the printer.

### Clear a K2 Vertical Transport Card Jam

a

- 1. Unlock the printer and open the printer access door.
- 2. Press the K3 rear access door release to open the rear access door.
- 3. Turn the K2 manual advance knob counterclockwise to move the jammed card inside the vertical transport until it is accessible through the rear access door.



Remove the card through the rear access door.



Close the printer doors and lock the printer.

### Clear a Flipper Card Jam

Unlock the printer and open the printer access door.

Press the K3 rear access door release to open the rear access

door.



Rotate the flipper module to access the card.

Remove the card through the rear access door.



Close the printer doors and lock the printer.

#### Clear an Embosser Card Jam

a

- 1. Unlock and open the embosser supplies access door.
- 2. Remove the indent ribbon and topping foil cartridges.
- 3. Rotate the manual advance knob inside of the embosser until the jammed card is accessible from the rollers.
- 4. Remove the card.




b

Replace the indent ribbon and topping foil cartridges. Close and lock the embosser supplies access door.

# Repair a Broken Ink Ribbon








# Repair Broken Retransfer Film

a





# Repair a Broken Indent Ribbon

a






# Repair Broken Topping Foil


a






### **Check the Power Connections**

#### **Printer Power Connections**



#### **Embosser Power Connections**



### **Check the Data Connections**

#### **Printer-to-Embosser Connection**



#### **Network Connection**



User Reference Guide 31

# **Common Printer LCD Messages**

Error Message	Refer to:	
112: Card hopper empty	"Load Cards in a Single-Hopper Printer" on page 5 "Use the Exception Slot" on page 6 "Load Cards in a Multi-Hopper Printer" on page 7 "Use the Multi-Hopper Exception Slide" on page 9	
166: C2 supply out or missing		
167: C2 supply not identified	"Replace the Retransfer Film" on page 14	
168: C2 supply not supported		
172: Improper shutdown	"Check the Power Connections" on page 30 "Check the Data Connections" on page 31	
175: C2 supply error	"Repair Broken Retransfer Film" on page 27	
234: K1 transport card jam	"Clear a K1 Horizontal Transport Card Jam" on page 21	
235: K2 transport card jam	"Clear a K2 Vertical Transport Card Jam" on page 23	
236: Flipper module rotate error	"Clear a Flipper Card Jam" on page 24	
237: C1 supply out or missing		
238: C1 supply not identified	"Replace the Color Ink Ribbon" on page 10, and "Replace the Cleaning Sleeve" on page 12	
239: C1 supply not supported		
240: C1 supply error	"Repair a Broken Ink Ribbon" on page 26	
277: Multi-hopper pick error	"Load Cards in a Multi-Hopper Printer" on page 7	

# **Common Embosser LCD Messages**

Error Message	Refer to:
127: Emboss transport error	"Clear an Embosser Card Jam" on page 25
133: Embosser card reject full	"Empty the Embosser Reject Tray" on page 20
135: Indent ribbon supplies out	"Replace the Indent Ribbon" on page 16
136: Indent ribbon break	"Repair a Broken Indent Ribbon" on page 28 "Replace the Indent Ribbon" on page 16
140: Embosser not available	"Check the Data Connections" on page 31
143: Topping foil problem	"Repair Broken Topping Foil" on page 29 "Replace the Topping Foil" on page 18
144: Topping foil out	
147: Topping foil no tag found	"Replace the Topping Foil" on page 18

### **Common Print Quality Concerns**

Problem	Cause	Solution
Non-repeating color dots on cards	Dust on the ink ribbon or retransfer film	Advance the supply, or
		"Replace the Color Ink Ribbon" on page 10
		"Replace the Retransfer Film" on page 14
Wrinkles appear on cards	Supplies are wrinkled	Advance the supply, or
		"Replace the Color Ink Ribbon" on page 10
		"Replace the Retransfer Film"     on page 14
Blurred or	Fingerprints, debris, or scratches on cards  Debris inside the printer  The printhead is dirty	Make sure cards are clean
discolored images		Clean the printer. Refer to the
Small unprinted areas on cards		"Cleaning Schedule" on page 35
areas on cards		"Replace the Cleaning Sleeve"
		on page 12
		• "Clean the Printhead" on page 43
Repeating color dots on multiple cards	Dust or debris on the cam rollers	"Clean the Printhead Cam Rollers" on page 47
Color or white streaks appear on cards	Dust or debris on the printhead	Print another card to see if the problem continues
		• "Clean the Printhead" on page 43

Refer to the CR825 and CE875 Instant Issuance System User's Guide for additional troubleshooting information.

Also refer to the "Cleaning Schedule" on page 35 for best-practices recommendations for maintaining the printer.

### **Cleaning Schedule**

Follow the recommended cleaning schedule to maintain the printer and obtain the best print quality.

Schedule	Action	Procedure
When you change the ink ribbon	Clean the printer with the isopropanol cleaning card.	<ul> <li>"Single-Hopper System" on page 36</li> <li>"Multi-Hopper System" on page 37</li> </ul>
	Replace the cleaning sleeve (C3).	"Replace the Cleaning Sleeve" on page 12
	Clean the printhead.	"Clean the Printhead" on page 43
If you see particles on completed cards	Replace the cleaning sleeve (C3).	"Replace the Cleaning Sleeve" on page 12
	Clean the printer with the adhesive cleaning card.	<ul><li> "Single-Hopper System" on page 39</li><li> "Multi-Hopper System" on page 40</li></ul>
If you see color or white lines on completed cards	Clean the printhead.	"Clean the Printhead" on page 43
If you see repeating color dots on completed cards	Clean the printhead cam rollers.	"Clean the Printhead Cam Rollers" on page 47



When you clean the printer using either the isopropanol or adhesive cleaning card, remove the ink ribbon (C1) and retransfer film (C2) cartridges, and the cleaning sleeve.

### Use the Isopropanol Cleaning Card

Use the isopropanol cleaning card regularly to clean the printer. Refer to the "Cleaning Schedule" on page 35.

#### **Single-Hopper System**

a

Unlock the printer and remove the supply cartridges and cleaning sleeve.

Open the input hopper and remove the unprinted cards. Handle the cards by the edges, or wear card inspection gloves.



Isopropanol Cleaning Card




Open the cleaning card package and remove the isopropanol cleaning card.

C

Load the cleaning card in the input hopper.

If the cleaning card appears bowed, insert it as shown.





d

Close the input hopper and lock the printer.


Continue with "Run the Isopropanol Cleaning Card" on page 38.

## Use the Isopropanol Cleaning Card (cont.)


## **Multi-Hopper System**

Unlock the printer and remove the supply cartridges and cleaning sleeve.

Remove the cleaning card from its package.



- 1. Pull out the multi-hopper exception slide and insert the cleaning card.
  - 2. Push in the exception slide.




Continue with "Run the Isopropanol Cleaning Card" on page 38.

## **Use the Isopropanol Cleaning Card (cont.)**

## **Run the Isopropanol Cleaning Card**

Use the LCD panel to run the isopropanol cleaning card.



- The isopropanol cleaning card moves into the embosser and is ejected in the embosser reject tray.
- Replace the supply cartridges in the printer, and the cards in the single input hopper.

# Use the Adhesive Cleaning Card

Use the adhesive cleaning card to remove particles that result from the retransfer process. Refer to the "Cleaning Schedule" on page 35 for information about when to use the adhesive cleaning card.


## **Single-Hopper System**

Unlock the printer and remove the supply cartridges and cleaning sleeve.

Open the input hopper and remove the unprinted cards. Handle the cards by the edges, or wear card inspection gloves.




Peel off the center strips on both sides of the adhesive cleaning card. Leave the side strips in place.



Load the adhesive cleaning card in the input hopper.

If the cleaning card appears bowed, insert it as shown.





Close the input hopper and lock the printer.

Continue with "Run the Adhesive Cleaning Card" on page 42.

## **Use the Adhesive Cleaning Card (cont.)**

#### **Multi-Hopper System**

Unlock the printer and remove the supply cartridges and cleaning sleeve.

b

- 1. Unlock the multi-hopper door lock.
- 2. Slide the lock bar release button (B1) to the left to release the hopper lock bars.
- 3. Rotate the center lock bar to the left to provide access to the H2 and H5 multi-hopper input cartridges.



C


- 4. Press the cartridge release button at the top of the H2 cartridge and open the cartridge door.
- 5. Lift the card weight to the top of the cartridge and gently pull it forward until it locks in position.
- 6. Remove the unprinted cards from the H2 cartridge. Handle the cards by the edges, or wear card inspection gloves.



## Use the Adhesive Cleaning Card (cont.)




Peel off the center strips on both sides of the adhesive cleaning card. Leave the side strips in place.



Load the adhesive cleaning card in the H2 cartridge and close the cartridge door.

If the cleaning card appears bowed, insert it as shown.







Do not insert the adhesive cleaning card in the exception slide of the multi-hopper.



Lock the multi-hopper.

- 1. Rotate the center lock bar to the right to the lock position.
- 2. Slide the lock bar release button to the right to lock the lock bars into place.
- 3. Lock the multi-hopper door lock.


g

Continue with "Run the Adhesive Cleaning Card" on page 42.

## Use the Adhesive Cleaning Card (cont.)

## **Run the Adhesive Cleaning Card**

Use the LCD panel to run the adhesive cleaning card.



Remove the adhesive cleaning card from the printer reject tray.

Replace the supply cartridges, and the cards in the input hopper of a single-hopper printer, or the H2 cartridge of a multi-hopper printer.

## Clean the Printhead


Clean the printhead each time you change the ink ribbon, or if you notice print quality concerns.

Use the following items to clean the printhead.






- 1. Power off and unlock the printer.
- 2. Open the printer access door and remove the ink ribbon (C1) and retransfer film (C2) cartridges.



#### Clean the Printhead (cont.)




Insert the lapping stick support into the printer. The support tool fits over the cartridge guideposts and slides into the printer.




Clean the printhead with the lapping stick.



Do not remove the pink lapping paper from the lapping stick.




1. Insert the lapping stick into the lower portion of the support tool. Slide it in until it stops.



## Clean the Printhead (cont.)

2. Move the lapping stick back and forth 3 times to clean the printhead.




- 3. Remove the lapping stick from the support tool.
  - You can use the lapping stick twice, one cleaning per side. Store the lapping stick after the first use.

d

Clean the printhead with the cleaning swab.

- 1. Open the cleaning swab package.
- 2. Insert the cleaning swab into the support tool. Center the swab as shown in the illustration (or toward the top of the support tool handle).




## Clean the Printhead (cont.)

- 3. Move the cleaning swab back and forth 3 times to remove any remaining debris from the printhead area.
- 4. Remove the cleaning swab from the support tool.



Remove the support tool from the printer.





- 1. Replace the ink ribbon and retransfer film cartridges and close and lock the printer access door.
- 2. Power on the printer.
- 3. Print one or more test cards to verify the print quality.



- Use only the lapping stick and cleaning swab to clean the printhead. Other materials can stick to the printhead and cause damage.
- Discard the lapping stick after the second use.
- Use the cleaning swab one time only. Discard the swab after cleaning the printhead.

## Clean the Printhead Cam Rollers

Use the adhesive cleaning card to clean the printhead cam rollers.




- 1. Power off the printer.
- 2. Unlock the printer and open the printer access door.
- 3. Remove the retransfer film cartridge (C2) from the printer.




b

Peel off the center and both side strips from one side of the adhesive cleaning card.



## Clean the Printhead Cam Rollers (cont.)

- C
- 1. Insert the cleaning card into the printer between the retransfer cartridge guidepost and the rollers. Make sure that the adhesive side of the card faces to the right and touches the rollers.
- 2. Move the cleaning card up and down along the rollers to remove debris.



- d
- 1. Replace the retransfer film cartridge.
- 2. Close and lock the printer.
- 3. Restart the printer.
- Discard the used cleaning card..

# **Notes**

**Notes** 

# **Notes**

**WARNING:** This product contains chemicals, including lead, known to the State of California to cause cancer, and birth defects or other reproductive harm. **Wash hands after handling.** 

WARNING: This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP), which is known to the State of California to cause cancer, and Di(2-ethylhexyl)phthalate (DEHP) and Butyl benzyl phthalate (BBP), which are known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov and www.datacard.com/califpropwarning.



Minneapolis, Minnesota 55379 952.933.1223 • 952.933.7971 Fax

www.entrust.com

Entrust, Sigma and the hexagon design are trademarks, registered trademarks and/ or service marks, and Datacard is a registered trademark and service mark, of the Entrust Corporation in the United States and other countries. All other trademarks are the property of their respective owners.

© 2016 - 2021. The design and information contained in these materials is protected